

HQ SERIES AIR-COOLED GASOLINE GEN-SETS

1. Use super light air-cooled Gasoline engine as power.
2. The products conform with relevant standards of IEC and their properties reach international level.



TECHNICAL DATA

Generator	Model	HQ1500H	HQ2900H	HQ4000H	HQ5000H	HQ6000H	HQ7000H
	Rated Frequency (Hz)	50 60	50 60	50 60	50 60	50 60	50 60
	Rated Output (KW)	1.3 1.5	2.0 2.2	2.5 3.0	3.0 3.5	4.0 4.5	5.0 5.5
	Max. Output (KW)	1.5 1.7	2.0 2.5	2.8 3.3	3.5 4.0	4.5 5.0	5.5 6.0
	Rated Voltage (V)	110, 115, 120, 220, 230, 240, 110/220, 115/230, 120/240					
	Power Factor (cos Φ)	1.0					
	Adjusting Voltage	Capacitance expiate/AVR adjusting					
Engine	Model	YH168F-A	YH168F-A	YH168F-B	YH173F	YH182F	YH188F
	Type	Single-cylinder, 4-stroke, forced air cooled					
	BoreXStroke (mm)	68X45	68X45	68X54	73X58	82X64	88X64
	Rated Output (KW/3000rpm)	3.1	3.1	3.8	5.1	7	8.3
	Ignition Fashion	Non-contact transistorized ignition					
	Starting Fashion	Manual/Electric					
	Fuel Capacity (L)	15	17	15	25	25	25
	Oil Capacity(L)	0.6	0.6	0.6	1.1	1.1	1.1
Unit	N. W/G.W (kg)	36/39	36/39	44/47	72/76	81/85	84/88
	Dimension(mm)	615X450X465	625X440X500	615X450X465	700X530X570	700X530X570	700X530X570