

AUDP SERIES SELF-PRIMING PUMPS

These pumps are suitable for suction from deep wells, and the series installed above ground with the pump body submerged guarantees functioning even when the static level of the well water falls as far as 9 meters below the level of the installed pump. For this reason these pumps are extremely reliable, economical and simple to use and find many uses in domestic where the suction depth exceeds the normal capacity (9 meters) for surface pumps.

PERFORMANCE AND WORKING LIMITS

Protection: IP 44
Insulation class F
Max. Pressure 10 bar
Max. Suction lift up to 8 m
Fluid temperature up to +40°C
Max. ambient temperature up to +40°C



TECHNICAL DATA

Model 220V 50Hz	Output KW	Total Head m	Size	F	Ejector Type	Suct.H m	Capacity L/min-At discharge head m			
							10m	15m	25m	35m
AUDP255A	2.55	40	1.25"X1"X1"	2.1	E20	10	50	34	12	8
					E20	15	34	20	5	5
					E30	20	17	13	7	4
AUDP370A	3.70	50	1.25"X1"X1"	2.4	E20	10		42	18	14
					E20	15		25	16	10
					E30	20		20	10	8
AUDP550A	5.50	55	1.25"X1"X1"	2.5	E20	15		38	24	15
					E30	20		30	17	10
					E30	30		21	12	7
AUDP750A	7.50	55	1.25"X1"X1"	4.6	E20	15		50	43	28
					E30	20		40	30	15
					E30	30		31	25	10