

HOPOW-YangDong

HOPOW-EPA Authentication

SERIES DIESEL GENERATOR SETS



HOPOW-YangDong SERIES DIESEL GENERATOR SETS

	HPY-8	HPY-10	HPY-12	HPY-16	HPY-20	
Model	HPY-8	HPY-10	HPY-12	HPY-16	HPY-20	
Rated Power(KW)	8	10	12	16	20	
ENGINE	Model	YSAD380D	YD480G	Y485G	YSD490D	Y4100G
	Rated output (kw)	10	13.5	16	21	25
	Governing method	Mechanical				
	Intaking method	Natural apirated				
	Fuel Consumption(g/kw.h)	247		248	247	
	Cooling Starting Method	Closed water cooled/electric starting				
GENERATOR	Model	HP-8	HP-10	HP-12	HP-16	HP-20
	Rated output (KVA)	10	12	15	20	25
	Rated Current(A)	14.4	18	21.7	28.9	36.1
	Rated Voltage(V)	400/230V				
	Frequency(HZ)	50/60 HZ				
	Power Factor(COS&)	0.8(lagging)				
	Phase / Connection	3-phase 4-wire Ytype connection				
	Excitation	Harmonic Excitation or phase Compound or brushless				
	Voltage Regulation	Manual/Automatic				
	Starting	Manual/Electric start				
Net Weight(kg)	650	700	750	800	900	
Packing size LWH(cm)	176x80x95	186x80x95	186x88x95	205x88x105	215x88x105	

HOPOW-EPA Authentication SERVERS DIESEL GENERATOR SETS

	EPA-8	EPA-10	EPA-12	EPA-15	EPA-20	
Model	EPA-8	EPA-10	EPA-12	EPA-15	EPA-20	
Rated Power(KW)	8	10	12	15	19	
ENGINE	Model	Y385G		Y485G	TY395D	
	Rated output (kw)		13.2	18.4	20	
	Governing method	Mechanical				
	Intaking method	Natural apirated				
	Fuel Consumption(g/kw.h)	240			220	230
	Cooling Starting Method	Closed water cooled/electric starting				
GENERATOR	Model	HP-8	HP-10	HP-12	HP-15	HP-20
	Rated output (KVA)	10	12	15	20	25
	Rated Current(A)	14.4/34.8	18/43.5	21.7/52.2	27.1/65.2	36/86.7
	Rated Voltage(V)	400/230				
	Frequency(HZ)	50/60HZ				
	Power Factor(COS&)	0.8(lagging)				
	Phase / Connection	3-phase 4-wire Ytype connection				
	Excitation	Harmonic Excitation or phase Compound or brushless				
	Voltage Regulation	Manual/Automatic				
	Starting	Manual/Electric start				
Net Weight(kg)	600	620	640	680	710	
Packing size LWH(cm)		160x72x110			170x72x120	